

NFC Tag Module

NFC Tag Module-NO battery needed type

NTM-100

The NTM-100 NFC Tag Module, operating distance can up to 30 mm, contactless transmission of data and supply energy, The NTM-100 NFC Tag no battery needed, applications for Bluetooth secure simple pairing using NFC.

Features

RF Interface (ISO/IEC 14443A)

- Contactless transmission of data and supply energy (no battery needed).
- Operating distance: up to 30 mm (depending on various parameters as e.g. field strength and antenna geometry).
- Operating frequency: 13.56 MHz.
- Fast data transfer: 106 kbit/s.
- High data integrity: 16-bit CRC, parity, bit coding, bit counting.
- True anticollision.
- 7 byte serial number (cascade level 2 according to ISO/IEC 14443-3).
- Compliant to NFCForum-AD-BTSSP_1.0
- RoHS compliant.
- Small outline: 25 x 25 x 0.8 mm.

EEPROM

- 168 bytes of total memory, divided in 42 pages (4 bytes each).
- 144 bytes of user r/w memory area, divided in 36 pages (4 bytes each).
- Field programmable read-only locking function per page 16 pages (64 bytes) of the memory.
- Field programmable read-only locking function per block (2 pages).
- 32-bit user definable One-Time Programmable (OTP) area.
- 16-bit counter.
- Data retention of 10 years.
- Write endurance 10000 cycles.

Security

- Anti-cloning support by unique 7-byte serial number for each device.
- 32-bit one way counter
- Field programmable read-only locking function per page for first 16 pages (64 bytes) of the memory.
- Read-only locking per block for rest of memory.

Applications

- Bluetooth Secure Simple Pairing Using NFC.

Outline

